BAUMAight

Turn your tractor or skidsteer into a

Brush Mulcher

Using our powerful, rugged Baumalight brush mulchers, you can effectively mulch large areas of brush and felled treetops without lifting a twig.





Brush mulchers take the hard work out of clearing brush. Attach the MF648 to your skidsteer for powerful mulching on low-flow hydraulics. Or use the PTO-driven MF860 for ultimate cutting power and unrivalled clearing capability.





MF648 Hydraulic Driven

Features:

- ▶ Powerful mulching on low-flow hydraulics (12-25gpm)
- ▶ 104 carbide-tipped teeth for longer tooth life, smoother operations and much finer mulch. Teeth can be installed in the field.
- ▶ Safety pusher bar to push trees and brush away from the mulcher and operator as they are being cut
- ▶ Rugged timer belt for long durability
- ▶ Control all functions from skid steer seat
- ▶ Ships with universal skid steer plate and flat-face hydraulic quick couplers

Specifications:

Unit weight: 1,250 lbs.

Unit dimensions: Cutting width—48" Overall width—62", Height—56"

RPM: Rotor RPM—1,200

MF860 PTO-Driven

Features:

carbide-tipped teeth

- ▶ Direct drive for the ultimate cutting power
- ▶ 126 carbide-tipped teeth for longer life, smoother operation and finer mulching. Teeth can be installed in the field.
- ▶ Safety pusher bar to push trees and brush away from the mulcher and operator as they are being cut
- Rugged timer belt and heavy-duty gearbox for long-term durability

Specifications:

Unit weight: 1,550 lbs.

Unit dimensions: Cutting width—60"

Overall width—75"

Height—58"

Tractor HP: Min—45, Max—70, Cat II

RPM: Rotor RPM—1,800 Input RPM—540

Maximum Recommended Brush Size

hydraulics:	12gpm	15gpm	20 gpm	25gpm
2,500 psi	1"	11/4"	1½″	2"
3,000 psi	11/4″	1½″	2″	2½″
double	all sizes f	or interm	ittent cut	ting

BAUMAight by

MTB MFG Inc.

4575 Powell Road, Wallenstein, Ontario N0B 2S0 Phone: 519.698.9864 Fax: 519.698.1087

E-mail: sales@baumalight.ca

for more products or dealer information see www.baumalight.ca

Maximum Recommended Brush Size

If drive system on tractor is	45нр	60нр	70нр		
in regular gear	3"	4"	5″		
in creeper gear	5″	6″	7″		
with hydrostatic transmission	8"	10"	12"		
double all sizes for intermittent cutting					

Baumalight sold by: